

Application No.: 09/760,593

Docket No.: S3100.0003/P0003

**REMARKS/ARGUMENT**

Claims 1-8 are pending in this application. Claims 1-8 stand rejected. By this Amendment, claims 1-8 have been amended. The amendments made to claims 1-8 do not alter the scope of these claims, nor have these amendments been made to define over the prior art. Rather, the amendments to claims 1-8 have been made to improve the form thereof. In light of the amendments and remarks set forth below, Applicant respectfully submits that each of the pending claims is in immediate condition for allowance.

Applicants note that the Office Action acknowledges the claim for priority under 35 U.S.C. § 119 however states that only some of the priority documents have been received. Applicants request that the Examiner enumerate which documents have not been received.

Paragraph 1 of the Office Action objects to Figures 12 through 15 as they do not contain a legend designating them as prior art. New Figures are submitted herewith with Figures 12 through 15 labeled as prior art.

Paragraph 2 of the Office Action objects to the Figures because numerals 15 and 51 are used to designate the base plate. Applicants have corrected this and submit herewith a replacement for Figure 9 where the base plate is relabeled as item 15.

Application No.: 09/760,593

Docket No.: S3100.0003/P0003

Paragraph 3 of the Office Action objects to Figure 1 because there is no description for element 11. Applicants submit herewith an amendment to the specification, specifically the paragraph beginning at line 9, on page 9, which includes a description of item 11.

Applicants request that the objections to the drawings be withdrawn as all of the objections have been corrected.

Paragraphs 4 and 5 of the Office Action object to the specification. Applicants have amended the abstract and disclosure in light of the Examiner's objections. A revised specification showing changes is attached as Appendix A. No new matter has been added.

Paragraph 7 rejects claims 1-4 and 7 under 35 U.S.C. § 112, second paragraph. Applicants have amended the claims in light of the Examiner's objections. Withdrawal of this objection is therefore requested.

Claims 1-8 stand rejected under 35 U.S.C. § 102(b) as being anticipated by U.S. Patent No. 4,610,185 ("France"). Applicants respectfully traverse this rejection.

To anticipate a claim under 35 U.S.C. § 102, the cited reference must disclose every element of the claim, as arranged in the claim, and in sufficient detail to enable one skilled in the art to make and use the anticipated subject matter. See, PPG Industries, Inc. v. Guardian Industries Corp., 75 F.3d 1558, 1566 (Fed. Cir. 1996); C.R. Bard, Inc. v. M3 Sys., Inc., 157 F.3d 1340, 1349 (Fed. Cir. 1998). A reference that does not expressly disclose all of the

Application No.: 09/760,593

Docket No.: S3100.0003/P0003

elements of a claimed invention cannot anticipate unless all of the undisclosed elements are inherently present in the reference. See, Continental Can Co. USA v. Monsanto Co., 942 F.2d 1264, 1268 (Fed. Cir. 1991).

A claimed aspect of the present invention is that a plurality of planes which concurrently contact the datum planes of the fitting jig are formed in the punch and the die in order to orient the punch and die with respect to each other. With the planes of the punch and the die thus constructed, it is possible to integrate the punch with the die by contacting the planes of the punch and the die with the datum planes of the fitting jig thereby orienting the punch relative to the die so as to coincide with the phases around the axis of the punch and the die. When the punch and die are oriented, the punch is fixed to the punch holder and the die is fixed to the supporting bit. After the punch and die are fixed to their respective supports, the fitting jig is removed from the punch and die. It is then possible to punch a hole in a workpiece by working the punch and the die.

In contrast, in France, the top shoe 12 faces the bottom shoe 14 and is guided by guide post 16 for upward and downward motion. The gage post 82 and the dowel 78 control rotation of the top shoe 12 and the bottom shoe 14 relative to the other about guide post 16 in a plane parallel to the base plate 62. France does not disclose forming planes in a punch and die and also does not disclose datum planes which contact the planes so as to orient the punch and die with respect to each other.

Application No.: 09/760,593

Docket No.: S3100.0003/P0003

Therefore, claims 1-8 are allowable over the France reference.

Applicants have responded to all of the rejections and objections recited in the Office Action. Reconsideration and a Notice of Allowance for all of the pending claims are therefore respectfully requested.

The amendments to the claims are for clarification purposes only and are not intended to limit the scope of the claims in any way. It is asserted that the present amendment places the application in a form for allowance. Entry of this amendment is therefore earnestly solicited.

If the Examiner believes an interview would be of assistance, the Examiner is welcome to contact the undersigned at the number listed below.

Dated: April 30, 2003

Respectfully submitted,

By 

Ian R. Blum

Registration No.: 42,336

DICKSTEIN SHAPIRO MORIN &  
OSHINSKY LLP

1177 Avenue of the Americas - 41st Floor  
New York, New York 10036-2714

(212) 835-1400

Attorneys for Applicant

IRB/mgs

SEP 04 2003 6:48 PM FR DSMO

TO 2245#193100#0003 P.14

Application No.: 09/760,593

Docket No.: S3100.0003/P0003

*marked  
copy  
copy*

**APPENDIX A**  
**Revised Specification and Abstract Under 37 CFR § 1.125**

65745 v1: 1#Q901!.DOC

Received from < > at 9/4/03 7:03:49 PM [Eastern Daylight Time]

S3100.0003

PUNCHING APPARATUS  
AND THE PUNCHING UNIT THEREOF

BACKGROUND OF THE INVENTION

Field of the Invention

5           The present invention relates to a punching apparatus which punches a hole at a predetermined location in a work piece by a punch constructed in a moving part (in general a ram) of a press working machine and a die constructed in a supporting part (in general a bed) of the press working machine. The present application also relates to a punching unit which is suited to the above punching apparatus.

10   Background Art

          Figs. 12 to 15 show a punching apparatus disclosed in the Japanese Patent Publication No. 2000-326296. In the punching apparatus shown in Figs. 12 to 15, a punch unit 26 which comprises a punch 26g is mounted on a punch holder (a moving part of the punching apparatus) 24 which is integrated into a non-rotatable rod 22 by bolts 23 and is fixed so as to be capable of rotating capably in rounding around the axis L along a direction of the punching operation within a predetermined angle (the angle described by the arc of the circular slot 24a in Fig. 13), also, the punching apparatus die unit 27g which comprises a die 27h is mounted on a die bed (a supporting part of the punching apparatus) 25 and is fixed so as to be capable of rotating around the axis L along the direction for the punching operation.

          As shown in Figs. 12 to 14, the punch unit 26 comprises an approximately circular base plate 2Gb integrated with a punch holder 24 integrated with a non-rotatable rod 22, by means of six fastening bolts 26a inserted and screwed through the slot hole 24a of the non-rotatable punch holder 24; a rectangular support plate 26d integrated with the base plate 26b by means of four fastening bolts 26c; a punch 26g having a rectangular cross-section integrated with a support plate 26d by means of two

screws 26e and two washers 26f; and a work presser foot 26k, integrated so as to be movable vertically (movable upward for a predetermined length from the position shown in Fig. 12) by means of four sets of a guide pin 26i and a ~~bush~~ bushing 26j.

The upper end of the each guide pin 26i is fixed to the base plate 26b, and the  
5 lower end of the each guide pin 26i slidably supports the work presser foot 26k in the vertical direction. The each bush 26j is attached to the work presser foot 26k and each bush 26j helps smooth the sliding of the guide pin 26i. Each spring unit ~~25h~~ 26h comprises a pin 26h1 integrated with the work presser foot 26k engages with the base plate 26b so as to be detachable in the upward direction and a compression coil Spring  
10 26h2 disposed around the pin ~~26h2~~ 26h1 and compressed between the base plate 26b and the work presser foot 26k. Here, the spring unit, the bush 26j, and the work presser foot 26k are shown only in Fig. 12.

As shown in Figs. 12 and 15, the die unit 27 comprises a base plate 27b integrated with the die holder 25 by means of four unit presser feet 27a; a rectangular  
15 support plate 27e integrated with the base plate 27b by means of four fixing bolts and two pins 27d; a die 27h, having a rectangular hole 27h1 into which the punch 26g can be inserted to a predetermined depth, integrated with the base plate 27b by means of two screws 27f and washers 27g; a circular die cover 27j integrated with the support plate 27e by means of two fixing bolts 27i. Each units presser foot 27a comprises a  
20 block 27a1 having a claw portion at the upper part for engaging with the support plate 27e, and a pin 27a2 and a pair of fixation bolts 27a3 for fixing the block 27a1 at a home position.

As shown in Figs. 12 and 15, the base plate 26b of the punch unit 26 and the base plate 27b of the die unit 27 are mutually connected by using four connecting pins  
25 28 and a pair of upper and lower ~~bushes~~ bushings 29 (fixed at each base plate) such that the punch 26g and the die 27h can integrally rotate by the same rotational phase (in the state where the punch 26g can accurately inter-fit the hole 27h1 of the die 27h). Each connecting pin 28 is fitted with each bush 29 so as to be able to be inserted into or drawn out from each other, so that the punch unit 26 and the die unit 27 can be  
30 independently replaced with other units.

In the above punching apparatus shown in Figs. 12 to 15, it is necessary to connect and relatively position the punch 26h to the die 27h by operating the four connecting pins 28 and eight ~~bushes~~ bushings 29. Furthermore, the ~~bush~~ bushing 29, the base plate 26b, the guide pin 26i and supporting plate 26d must be arranged  
5 between the punch 26g and each connecting pin 28, and the ~~bush~~ bushing 29, the base plate 27b, the pin 27d and the supporting plate 27e must be arranged between the die 27h and each connecting pin 28.

Because it is necessary to operate so many parts (the four connecting pins 28 and the eight ~~bushes~~ bushings 29) in order to relatively position the punch 26g and the  
10 die 27h, the costs and man-hours required to constructing the punch 26g and the die 27h are increased. Because there are such many parts (the support plate 26d, the guide pin 26i, the base plate 26b, the ~~bush~~ bushing 29 for punch 26g, the connecting pins 28, the ~~bush~~ bushing 29 for the die 29 27, the base plate 27b, the pin 27d, the supporting plate 27e and etc) between the punch 26g and the die 27h, the dimensional errors of  
15 each parts accumulate. Because the ~~bush~~ bushing 29 located on the upper end of the connecting pin 28 supports the punch 26g and the ~~bush~~ bushing 29 located on the lower end of the connecting pin 28 supports the die 27h, the space between the punch 26g and the die 27h becomes to be too much to exactly position the punch 26g relative to the die 27h.

## 20 SUMMARY OF THE INVENTION

The present invention was made in the view of the above-mentioned problems.

According to one aspect of the present invention, in a punching apparatus for punching a hole at a predetermined location on a work piece by means of a punch integrated into anyone of a moving part of a press working machine and a supporting  
25 part of the press working machine and a die integrated with another one of the moving part and the supporting part, each of the punch and the die has a plurality of planes for fitting, fitted with datum planes of a fitting jig.

In the above punching apparatus, it is possible for the punch and the die to be positioned with respect to each other by fitting each of the planes for fitting of the



punch and the die with the datum planes of the fitting jig. The present invention is ~~preferable~~ preferably for a punching apparatus which punches a non-circular hole such as a rectangular hole.

It is possible ~~for~~ to mutually position the punch and the die using the fitting jig  
5 which is the only inclusion between the punch and the die. Therefore the punch is integrated into a moving part of a press working machine with a high accuracy and the die is also integrated into a supporting part of the press working machine with high accuracy, and it is possible to punching a hole into a work piece with high accuracy after removing the fitting jig from the punch and the die.

10 The ~~Because the above~~ positioning for the punch and the die with respect to each other is completed by fitting the plane for fitting of the punch with the datum plane of the fitting jig and fitting the each plane for fitting of the die with the datum plane of the fitting jig, thus it is possible to minimize the parts for the fitting operation, reduce the product cost, and also expedite construction by reducing the steps for a  
15 fitting.

The ~~When the~~ punch and the die are capable of rotating, independently of the moving part and the supporting part, around an axis which lies parallel to a direction for the punching, and cannot rotate relative to each other by touching the planes for fitting with the datum planes of the fitting jig, therefore it is possible to position the  
20 punch and the die at a desirable rotating position, ~~which is another merit of the present invention.~~

When the planes for fitting are along the direction for punching and cross each other in a right angle, it is possible to simplify the a construction of the fitting jig by aligning the planes for fitting of the punch and the die in a single plane and fitting the  
25 planes for fitting with the same datum planes of the fitting jig, thereby reducing the cost for. manufacturing the fitting jig.

According to another aspect of the present invention, in a punching unit for a punching apparatus, each of a punch and a die has plurality of planes for fitting and a fitting jig has datum planes fitted with the planes for fitting of the punch and the die.

Therefore the punch and the die can be mutually positioned by fitting the each planes for fitting of the punch and the die with the datum planes of the fitting jig.

If the punch and the ~~dies can be rotating~~ die can rotate independently of the punching machine around an axis along the direction for punching and can also be  
5 rotated together in a state where the datum planes of the fitting jig are attached with each of the planes for fitting of the punch and the die, it is possible for positioning the punch and the die at a desirable position through the direction for rotating.

It is preferable for the fitting jig to have a U-shaped cross section having a pair of arms on one inner surface of which one of the datum planes is arranged and on the  
10 other one inner surface of which the other one of the datum planes is arranged in order to hold the punch and die ~~there between~~ the pair of arms and also order to fit the planes for fitting of the punch and the die with the datum planes of the fitting jig while rotating about the axis.

#### BRIEF DESCRIPTION OF THE DRAWINGS

15 Fig. 1 is a front view of a punching apparatus of a preferred embodiment of the present application.

Fig. 2 is a plane view of the punching apparatus which is disclosed in Fig. 1.

Fig. 3 is a partly cross-sectional front view of the puncher portion of the punching apparatus in which a punch unit and a die unit are integrated.

20 Fig. 4 is a plane view of the punch unit disclosed in Fig. 3.

Fig. 5 is a bottom view of the punch unit disclosed in Fig. 3.

Fig. 6 is a partially cross-sectional view of the punch unit which shows the relationship between a supporting plate for a stripper, a supporting flange for a striper and a positioning pin.

25 Fig. 7 is a bottom view of the punch unit disclosed in Fig. 3.

Fig. 8 is a plane view of the die unit disclosed in Fig. 3.

Fig. 9 is a partially cross-sectional view of the punch and the die disclosed in Fig. 3 while relatively positioning the punch with the die by a fitting jig.

Fig. 10 is a cross-sectional view of the fitting jig and the die unit disclosed in Fig. 9 during the relative positioning.

Fig. 11 is a front view of the fitting jig disclosed in Figs. 9 and 10.

Fig. 12 is a partially cross-sectional view of a punching apparatus of an example of a background art in which a punch unit and a die unit are constructed with a connecting pin.

Fig. 13 is a plane view of a punch holder disclosed in Fig. 12.

Fig. 14 is a bottom view of the punching unit disclosed in Fig. 12 in which the spring unit, the bush and the supporting plate are removed.

Fig. 15 is a plane view of the die unit disclosed in Fig. 12.

#### DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, one embodiment of the present invention is described. The punching apparatus shown in Figs. 1 to 11 is suitable for punching of a wide variety of few sheet-shaped work pieces. The punching apparatus comprises a work supporting portion A0 (not shown in Fig. 1) for supporting a work piece (not shown in the figures), a ~~puncher~~ punching portion 10, and an image pickup portion B0.

The work supporting portion A0 is used for supporting the work at a predetermined position by clamping and is mounted on a  $\theta$  direction transfer mechanism A2, which is mounted on the upper movable carriage A1, so as to be able to fixed around a pivot p in a horizontal plane. The upper movable carriage A1 is mounted on a machine base A6 through an X-axis direction transfer mechanism A3, an intermediate movable carriage A4, and a Y-axis direction transfer mechanism A5 so as to be movable in two directions (the X-axis direction and Y-axis direction) in a horizontal plane.

The  $\theta$  direction transfer mechanism A2 comprises a supporting axis A2a vertically arranged on the work supporting portion A0, and a servo motor which drives the supporting axis A2a. The  $\theta$  direction transfer mechanism is capable of driving or stopping the work supporting portion A0 at an arbitrary angle about the pivot.

The X-axis direction transfer mechanism A3 comprises a pair of guide rails A3a mounted on the intermediate movable carriage A4 for supporting the upper movable carriage A1 slidably in the X-axis direction, a screw feed mechanism A3b arranged between the both guide rails A3a for feeding the upper movable carrier A 1  
5 in the X-axis direction, and a servo-motor A3c connected with one end of a lead screw of the screw feed mechanism which drives the lead screw, such that the upper movable carrier A1 can be positioned in the X-axis direction by controlling the rotation of the servo-motor A3c by a controller (not shown).

The Y-axis direction transfer mechanism A5 comprises a pair of guide rails  
10 A5a mounted on a machine base A6 for supporting the intermediate movable carrier A4 slidably in the Y-axis direction, a screw feed mechanism A5b which is arranged between the two rails A5a for transferring the intermediate movable carriage A4 in the Y-axis direction, and a servo-motor A5c connected with one end of a lead screw of the screw feed mechanism A5b which drives the lead screw, such that the intermediate  
15 movable carrier A4 can be positioned in the Y-axis direction by controlling the rotation of the servo-motor A5c by the controller (not shown).

The ~~puncher~~ punching portion 10 is a portion for executing rectangular hole punching for a predetermined portion of a work piece. As shown in Figs. 1 and 3, the ~~puncher~~ punching portion 10 comprises a punch holder 14 and a die accepting base 15  
20 arranged on the machine base A6 so as to oppose to the punch holder 14. The punch holder 14 is integrated with a bottom end of a rod 12 (not rotatable) using three bolts (not shown) in the same manner as the punch holder 24 of Figs. 12 to 15 by using the bolts 23. The rod 12 is driven by an elevation device 11 so as to move upward and downward. The puncher holder 14 comprises four slot holes (not shown in the  
25 figures) in the form of a circular arc which correspond to the slot holes 24a shown in Figs. 12 and 13. A punch unit 16 is assembled with the punch holder 14 and can rotate about the axis L which lies parallel to the punching direction within a predetermined angular range. A die unit 17 is assembled with the die accepting base 15 and is capable for rotating around the axis L. The punch unit 16 can also be fixed  
30 to the punch unit 16 and the die unit 17 can also be fixed to the die accepting base 15.

The punch unit 16 comprises a circular punch holding flange 16a which is integrated with the punch holder 14 by screwing bolts (not shown in figures) which correspond to the bolts 26a in Figs. 12, 13 and 14, through a slot hole (not shown in the figures) in a form of circular arc in the punch holder 14 which is non-rotatably integrated with the non-rotatable rod 12 and punch 16d which is integrated with the punch holding flange 16a by using two bolts 16b and two location pins 16c.

The punch unit 16 also comprises a rectangular stripper attaching plate 16h which is movably integrated with the punch holding flange 16a through the L axis direction in a predetermined length by using four units of spring 16e, four guide pins 16f and bushes 16g, a stripper holding flange 16k integrated with the stripper attaching plate 16h by using four bolts 16i (shown in Fig. 5) and two locating pins 16j (shown in Figs. 5 and 6), a stripper 16n integrated into the stripper supporting flange 16k by using four bolts 16m. A through hole 16nl through which the rectangular projection 16dl on a bottom end of the punch 16d passes is formed in the stripper 16n each small diameter portion of the locating pins 16j is ~~lightly~~ tightly fitted to the stripper attaching plate 16h and assembled to the stripper attaching plate by using four bolts ~~16j1~~ 16j1 and washers 16j2.

As shown in Fig.3, the bottom end of each of the guide pin 16f is tightly fitted into the stripper attaching plate 16h and an upper end of each guide pin is slidably fitted into the ~~bush~~ bushing 16g. As shown in Fig. 3, each spring unit 16e comprises a free washer 16e1 assembled in a hollow of the stripper attaching plate 16h, a collar 16e3 and a fixed washer 16e4 assembled into the stripper attaching plate 16h by using bolts 16e2 and a compressing coil spring 16e5 arranged between the free washer 16e1 and the punch holding flange 16a.

As shown in Figs 3 and 6 2, the die unit 17 comprises a base plate 17b integrated with the die holder 15 by means of two pressers 17a; a die 17d integrated with the base plate 17b using four bolts 17c and having a central rectangular hole 17dl into which the rectangular projection ~~16dl~~ 16dl of the punch ~~16n~~ 16d is inserted to a predetermined length; a circular die surrounding spacer 17g integrated with the base plate 17b, by using two bolts 17e and two ~~sym-plate~~ plates 17f, and having a

rectangular hole 17g1 which encloses the die 17d; a die cover 17h integrated with the die holder 15 using four bolts 17i and having a circular hole 17h1 which encloses the die surrounding spacer 17g. Each presser 17a comprises a block 17a1 having a claw portion which engages with the base plate 17b in an upper portion. The each unit  
5 presser 17a also has a pin 17a2 and a pair of bolts 17a3 which fix the block 17a1 to a predetermined position.

Image ~~The image~~ pickup portion B0, ~~which~~ detects the position of the work piece clamped by the work supporting portion A0 (detects the displaced amounts from the reference location of the work in the X-axis, Y-axis, and the  $\theta$  directions), and  
10 provides a camera B1 for outputting analog image signals to an image processing controller (not shown). The image processing controller obtains the locations of two points marked on the work piece through the image analysis of the image signals, calculates each locational displacement in the respective X, Y and  $\theta$  directions, and outputs these displacements to a monitor (not shown).

15 Furthermore, the displacement of the work can be compensated using the  $\theta$  direction transfer mechanism A2, the X direction transfer mechanism A3 and the Y direction transfer mechanism A5 for restoring the work piece to the home position (to minimize the displacement in each direction). It is to be noted that the compensation of the displacement can be carried out by an automated operation.

20 The punching apparatus thus constructed according to the present embodiment is capable of providing the steps of compensating the work location, in the state that the punch unit 16 and the die unit 17 are set into the predetermined positions (shown in Fig.3), into the home position prior to the punching operation by use of the  $\theta$  direction transfer mechanism A2, the X direction transfer mechanism A3, and the Y  
25 direction transfer mechanism A5, and carrying out the punching operation by means of the punch 16d and the die 17d (when a plurality of holes are to be punched, the punching operations are sequentially carried out). When the punching operation is to be carried out for a predetermined number of work pieces, the above process is repeatedly executed. In this case, if the automated work supply and delivery can be

carried out with high accuracy of positioning, the operation to ensure that the work piece is in the ~~work-to-the~~ home position can be omitted.

In the embodiment shown in Figs. 7 and 9, the punch 16d comprises two planes for fitting S1 which lie parallel in the direction of the punching operation (vertical  
5 direction) and are in right angles to each other, as shown in Figs. 8, 9 and 10, the die 17d comprises two planes for fitting S2 which lie parallel in the direction for punching operation (vertical direction) and are in right angles to each other. Therefore the punch 16d and the die 17d are positioned with a jig body 18a by attaching the planes S1 and S2 with two datum planes S0 of the jig body 18a. A fitting jig 18 comprises  
10 the jig body 18a having a U-shaped cross section and the two datum planes S0, and a pair of E-shaped fixing plates 18b each of which is mounted on the jig body 18a by two bolts 18c. The datum planes S0 are located on an inner surface of the jig body 18a and are set to enclose the punch 16d and the die 17d across an open side of the U shaped cross section, therefore the fixing plates 18b are fitted with the jig body 18 thus  
15 constructed.

The punch 16d can be located and fitted (setting at a predetermined position) relative to the die 17d by the following steps.

- i. Connecting the punch 16d with the die 17d ~~by~~ with the fitting jig 18 in a state where the four bolts 17a3 of the die unit 17 are loosened before  
20 integrating the stripper supporting flange 16k and stripper 16n of the punch unit 16 with the die surrounding spacer 17g and the die cover 17h of the die unit 17.
- ii. Attaching a plane for fitting S1 of the punch 16d and a plane for fitting S2 of the die 17d with the datum planes S0 of the fitting jig 18, then the  
25 punch 16d is positioned relative to the die 17d.
- iii. Screwing the four bolts 17a3, the punch 16d and the die 17d thus positioned with respect to each other are fitted at a predetermined position and the locating and the fitting for the punch and the die are completed.

The fitting jig 18 is the only intervening part between the punch 16d and the die 17d throughout the above relative positioning and fitting. Therefore it is possible to fit the punch 16d into the punch holder 14 as a moving portion of a press working machine with a high accuracy, and it is also possible to fit the die 17d into the die supporting bed 15 as a supporting portion of the press working machine. After the fitting of the punch 16d and the die 17d is completed, the fitting jig 18 must be removed from the punch 16d and the die 17d. A manufacturing operation for the punching apparatus is completed by fitting the stripper supporting flange 16k and the stripper 16n with the stripper attaching plate 16h and fitting the die surrounding spacer 17g and the die cover 17h with the base plate 17b. The punching apparatus in which the punch 16d and die 17d are thus constructed can punch a hole at a predetermined position on a work piece with high accuracy.

Because the above relative positioning for the punch 16d and the die 17d is completed by the steps of: setting and removing the only one fitting jig; fitting each plane for fitting S1 of the punch 16d with each datum plane S0 of the fitting jig 18; and fitting each plane for fitting S2 of the die 17d with each datum plane S0 of the fitting jig 18, it is possible to minimize the number of parts used for the fitting operation, reduce the product cost, and also expedite the manufacturing processes by reducing the steps for fitting.

Because the plane for fitting S1 of the punch 16d and the plane for fitting S2 of the die 17d lie parallel to the direction of the punching operation and cross each other at a right angle, each of the two datum planes S0 of the fitting jig 18 are suitable for anyone of the planes for fitting S1 and S2, and it is possible to simplify the structure of the fitting jig 18 (see the figures) and reduce the production cost.

It is noted that the punch 16d and the die 17d of the above embodiment are integrally rotatable about the axis L which is parallel to the direction for punching by loosening the four bolts 17a3, therefore it is possible to fit the punch 16d and the die 17d thus positioned with respect to each other by screwing the four bolts 17a3.

Besides the mechanism in the above embodiment in which the punch 16d and the die 17d can continuously rotate about the axis L, another mechanism such as a



mechanism for rotating stepwise by a predetermined angle is available for the punching apparatus. It is also possible to tightly fit the punch 16d with the punch holder 14 and loosely fit the die 17d with the die supporting bed 15 in order to position the die 17d and the punch 16d with respect to each other by using the fitting jig 18.

5 Besides the mechanism in the above embodiment in which the plane for fitting S1 of the punch 16d and the plane for fitting S2 of the die 17d are arranged at tight angles and lie parallel to the direction for punching, fitting planes suitable for attaching to datum faces (not limited to vertical planes) which are formed in the fitting jig 18 or other types of positioning planes can also be used in the present invention.

10 Besides the punching apparatus in the above embodiment in which the direction of the punching operation is vertical, a punching apparatus in which the operating direction is horizontal or a punching apparatus in which the operating direction inclines to the vertical punching operation can be used in the present invention. Besides the punching apparatus in the above embodiment in which the  
15 punch 16d is set in the moving portion (the punch holder 14) of the punching apparatus and the die 17d is set in the supporting portion (the die holder 15) of the punching apparatus, a punching apparatus in which a punch is set in the supporting portion and the die is set in the moving portion can also be used.

~~In one~~ Besides the punching apparatus in the above embodiment, in which  
20 each of the punch and the die comprises the has planes for fitting to fit the datum planes of the fitting jig ~~and also to integrally~~ which are round, Alternately, a fitting jig which is directly fitted with the planes for fitting of the punch and the die so as to position the punch and die with respect to each other is also available. For instance, a  
rod having a U-shaped profile and rectangular cross section can be used for  
25 positioning a punch and a die with respect to each other. The rod comprises a pair of arms, one of which is to be inserted into a rectangular hole which is arranged in the plane for fitting of the punch and directs to the axis L, the other one of which is to be inserted into a rectangular hole which is arranged in the plane for fitting of the die and directs to the axis L. The punch and the die can be fitted and positioned with respect  
30 to each other by inserting the arms of the rod into the holes of the punch and the die.

S3100.0003

PUNCHING APPARATUS  
AND THE PUNCHING UNIT THEREOF

ABSTRACT

A punching apparatus is provided which can punch a non-circular holes at a predetermined position of a work piece. In the punching apparatus for punching a hole by means of a punch integrated into anyone of the moving part of a press working machine or the supporting part of the press working machine, and a die integrated with the other one of the moving part and the supporting part; each of the punch and the die has plurality of planes to be fitted with datum planes of a fitting jig. The punching unit for the punching apparatus comprises a punch, a die, and a fitting jig for positioning the punch and the die with respect to each other, wherein each of the punch and the die has plurality of faces for fitting and the fitting jig has datum planes to be fitted with the planes for fitting of the punch and the die.